

## Shell Kit Aqualift S Compact black GTF1200 Mono



### Article information

Item no.: 280501S-RBK

GTIN: 4026092106945

Price group: 20

### Description

For combination with a KESSEL technology kit for creating a Mono lifting station for wastewater without sewage with a GTF1200 wastewater pump. The ready to plug in lifting station for wastewater without sewage is equipped with a submersible pump and a backflow preventer. The collection tank made of permanently resistant polymer (PE) has an open pump tank. One-handed closures enable easy removal of the integrated components. The system for installation in the floor slab is pre-assembled for final installation on site. KESSEL shell kit consisting of:

- With vertically adjustable upper section for continuous height and level compensation and integrated floor drain - PE collection tank, resistant to aggressive wastewater and 3 m groundwater - Includes backflow preventer for the pressure pipe - Includes connection socket for inlet and conduit pipe

#### Variant

Type of system:

Single unit

Rim width:

Float switch

Backwater protection:

integrated

#### General characteristics

Colour:

black

Standard:

EN 12050-2

Type of wastewater:

without sewage

Installation situation:

floor slab installation

Delivery state:

Installation-ready (connection parts must be connected on site)

#### Dimensions

Net weight:

15,7 kg

Gross weight:

15,7 kg

Groundwater resistant from lower edge of base section:

3000 mm

Installation depth:

490 - 620 mm

|                                |                                     |
|--------------------------------|-------------------------------------|
| Vertical adjustment:           | vertically adjustable upper section |
| Length:                        | 617 mm                              |
| Width:                         | 585 mm                              |
| Packaging dimension:           | length                              |
| Packaging dimension:           | width                               |
| Packaging dimension:           | height                              |
|                                |                                     |
| Tank/drain body                |                                     |
| Pressure pipe connection (DN): | 32                                  |
| Pressure pipe connection (OD): | 40 mm                               |
| Inlet nominal size (DN):       | 100 mm                              |
| Pumping volume:                | 16 l                                |
| Tank volume:                   | 65 l                                |
|                                |                                     |
| Coverage features              |                                     |
| Type of cover:                 | Cover plate with slotted cover      |
| Cover material:                | Polymer                             |
| Colour of cover:               | black                               |
| Width of cover:                | 366 mm                              |
| Length of cover:               | 366 mm                              |
| Drainage function:             | yes                                 |
| Cover locking:                 | Lock & Lift                         |
| Load class:                    | K 3 (EN 1253-1)                     |
| Max. flooring height:          | 16 mm                               |
|                                |                                     |
| Pumping device                 |                                     |
| Pump control:                  | GTF 1200                            |
| Number of pumps:               | 1                                   |
| Max. pumping height:           | 9 m                                 |