

Scada wall drain w/cov, conc, fixed w/prf membrn



Article information

Item no.: 48000.01M GTIN: 4026092079119 Price group: 10

Advantages

- Flexible & convenient installation options
- Membrane flange attached in the factory

Description

The Scada wall drain is suitable for indoor floor drainage and provides connection options at the front, left and right-hand side.

Variant

Lighting: without

Waterproofing layer on the drain body: Factory-fitted sealing collar (WaD) according to DIN

18534

Water supply: W3-I
Sealing water height: 22 mm
Discharge rate (l/s) with 20 mm backwater: 0,5

General characteristics

Nominal size (DN): 50 Outer diameter (OD): 58 mm

Dimensions

Net weight: 1,8 kg Gross weight: 2,31 kg Length: 362 mm Width: 195 mm Height: 353 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: ABS

Coverage features

Type of cover: Scada drain cover

Colour of cover: selectable



Height of cover: 61 mm
Length of cover: 296 mm
Min. flooring height: 15 mm

Frame material: Stainless steel 14301

Cover locking: inserted
Grating colour: Invisible
Max. flooring height: 15 mm
Shape of upper section: square
Upper section material: ABS
Odour trap: included