


## Backwater valve Staufix DN 100, Floor slab, black, Type 2 R





## Article information

Item no.: 730100.10SR GTIN: 4026092076378

Price group: 10

## **Advantages**

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

## **Description**

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

Variant

Stainless steel flap as rat protection: yes
Emergency closure: yes
Mechanical backwater flaps: 2

General characteristics

Colour: black
Standard: EN 13564
Nominal size (DN): 100
Outer diameter (OD): 110 mm

Type of wastewater: without sewage Installation situation: floor slab installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Backwater protection: Type 2

Dimensions

Net weight: 6,5 kg



Gross weight: 9,1 kg Groundwater resistant from lower edge of base 3 mm

section:

Cutout dimension, width: 750 mm
Cutout dimension, length: 750 mm
Vertical drop between inlet and outlet: 8 mm

Installation depth: 287 - 410 mm

Vertical adjustment: vertically adjustable upper section

Length: 444 mm
Width: 444 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Coverage features

Type of cover:

Cover material:

Polymer

Colour of cover:

black

Width of cover:

366 mm

Length of cover:

Cover locking:

Lock & Lift

Load class:

Lock & Lift

Tightness: surface water resistant