

Practicus drain body Press. fl., DN 100, Horizontal outlet



Article information

Item no.: 45119
GTIN: 4026092033791
Price group: 10

Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- absolutely corrosion-free and durable material

Description

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

| | |
|---|---|
| Variant | |
| System: | 125 |
| Waterproofing layer on the upper section: | Enclosed sealing collar to be glued (bd) according to DIN 18534 |
| Waterproofing layer on the drain body: | Press sealing flange (suitable for creating watertight seals) |
| Sealing water height: | 50 mm |
| General characteristics | |
| Nominal size (DN): | 100 |
| Outer diameter (OD): | 110 mm |
| Dimensions | |
| Net weight: | 1,83 kg |
| Gross weight: | 2,12 kg |
| Diameter: | 273 mm |
| Height: | 147 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Tank/drain body | |
| Number of outlets: | 1 |
| Connection inlet/outlet sockets: | The outlet spigot is suitable for connection to SML pipes. |
| Material of drain body: | PP |

| | |
|-------------------|----------|
| System: | lateral |
| Coverage features | |
| Odour trap: | included |